

Rectifier RSU N

Ultra highly reliable power supply module



Rectifier RSU NC3000

Highlights

- | Up to 220 VDC
- | 19" 2U / 3U size variants
- | Front side connectivity
- | Fault tolerant software
- | Ultra highly reliable power supply unit
- | Wide temperature range of operation

RELIABLE. CONVENTIONAL. HARD.

Rectifier RSU N – rectifier and battery charger for stand-alone use.

Performance

The power supplies of RSU N series present a highly reliable and compact battery charging rectifiers with front side connectivity. The rectifier can be used for all DC applications with or without a battery.

Simplicity

Easily done. Setting up and controlling via 1 button beside the display.

Reliability

Tested functionality under harshest conditions. Up to 80°C.

Intelligence

Integrated battery testing procedures and failure detection methods.

Monitoring and control

Communication via HTTP, SNMP. Integrated web server and IPS' global cloud monitoring.

Features

- Recharge all types of batteries
- Battery asymmetry control
- Voltage temperature compensation
- Temperature measurements
- Fan speed regulation
- Light and sound signaling
- Surge protection
- Protection against overvoltage
- Protection against short circuit
- Protection against deep battery discharge

Technical data

Rectifier RSU N series

Rectifier module	RSU NA	RSU NB	RSU NC	RSU ND	RSU NE	RSU NF
Input (AC)						
Voltage, nominal	230 V					
Voltage, operating range*	70 V ... 292 V					
Frequency	0 Hz ... 80 Hz					
Power factor	> 0.99					
Output (DC)						
Voltage	12 V	24 V	48 V	60 V	110 V	220 V
Power, maximum	3000 W					
Current, maximum	250 A	125 A	62.5 A	50 A	27.3 A	13.6 A
Other specifications						
Main functions and features	Recharge and maintain all types of batteries Battery test and asymmetry control Voltage temperature compensation Fan speed regulation (current and temperature) Digital, light and sound signaling					
Protections	Protection against over-voltage and disturbances at the input Protection against overload and short circuit at the output Protection against deep battery discharge Protection against high temperature					
Maximum power for 2U size variant	1300 W (RSU S series)					
Maximum power for 3U size variant	3000 W					
Dimensions for 2U (WxHxD) mm	(440x88x262)					
Dimensions for 3U (WxHxD) mm	(440x132x262)					
Mounting option 1	Horizontal, (2U / 3U) across 19" or ETSI rack					
Mounting option 2	Standalone					
Operating conditions						
Ambient temperature	-40°C ... +80°C					
Operating altitude	≤ 3000 m a.s.l.					

*Power de-rating @ 70-140 VAC



Rectifier RSU SB1000, height 2U

IPS International Power Supply